

Container Handler

Used Container Handler Inglewood - Container handlers, also known as cargo ships and container ships transport their load in a large intermodal container. This type of shipping is called containerization and it is a specific kind of freight transport that carries non-bulk types of seagoing cargo. Container ship capacity is measured in units that are equal to 20' equivalent loads. Typical loads range with a mixture of 20-foot and 40-foot containers. Container ships are responsible for transporting roughly ninety percent of non-bulk items across the globe. These ships are one of the main oil tanker rivals due to their size as one of the biggest seaworthy ships. There are two main categories for dry cargo which are break-bulk and bulk cargo. Grain and coal fall into the bulk cargo category. They are often moved in their raw form, package-free in large volumes in the hull of the ship. Break-bulk cargo items normally consist of manufactured goods that are transported in packages. Before the 1950s when containerization hadn't been invented yet, break-bulk materials were loaded, secured and unattached one piece at a time in a very time-consuming process. Grouping cargo into containers allows for 1000-3000 cubic feet of cargo to be simultaneously moved once every container has been secured with standardization techniques. Efficiency has tremendously increased break-bulk cargo shipping. Thanks to these new systems, shipping time has been reduced by eighty-four percent and costs have come down by roughly thirty-five percent. Approximately 90% of non-bulk items were shipped in containers in 2001. In the 1940s, the first container ships were made from tankers that underwent conversion after World War II. Container ships eliminate the individual holds, hatches and dividers normal within traditional cargo vessels. Essentially the container ship's hull is similar to a huge warehouse that uses vertical guide rails to divide it into cells. The cargo in the containers is held by these specially designed cells. Most shipping containers are constructed from steel; however, additional materials including plywood, fiberglass and wood are used. Many containers are categorized by their size and function since they are designed to be transferred to and from trucks, trains, coastal carriers, semi-trailers and more. Even though the shipping industry has been transformed by containerization, it took some time to streamline the process. Initially, ports, railway companies and shippers were concerned regarding the extensive costs that came with constructing infrastructure, ports and railways required to accommodate the cargo ships and transporting items with rail and roads. Numerous trade unions were concerned that containers would affect port jobs and manual labor associated with cargo handling for dock and port workers. There was a decade of legal battles prior to the container ships starting international service. By 1966, after the first container liner service began from Rotterdam, Netherlands to the USA, cargo shipping was transformed. Loading and unloading of cargo ships has been reduced to a few hours instead of the days it used to take traditional cargo vessels. Along with cutting labor finances, it has shortened shipping times between ports to a large extent. Nowadays, it takes only weeks as opposed to months for items to be delivered from Europe to India and vice versa. Generally, there is less damage to materials thanks to less frequent handling. Securing loads properly also helps with less cargo shifting during transport. Before shipping, containers are closed and only opened after they arrive at their new location to prevent theft and damage. There has been greater international trade growth due to the reduced shipping expenses and travel time delivered by container ships. Sealed factory containers now carry cargo that used to arrive in barrels, cartons, crates, bags and bales. Scanning machines work with computers to trace the product code on the contents. Technology has made this tracking system accurate and exact to enable a two week voyage to be timed for arrival within an accuracy rate of under fifteen minutes. Manufacturing times and delivery have been greatly enhanced with these advancements. Raw materials are delivered in less than an hour in sealed containers within an hour prior to being utilized for manufacturing. This results in more accuracy and less inventory costs. Shipping companies provide boxes to the exporters for loading merchandise into. Items are delivered into the docks by road or rail or a combination to be loaded onto cargo ships. Containerization has streamlined the process of loading by

reducing the number of workers and hours it takes to fit cargo into their holds. Cranes are used in the shipping industry or on the pier to organize containers. Once the hull has been completely loaded, more containers can be secured onto the deck. Efficiency has been one of the main design elements for cargo ships. Containers may travel on break-bulk vessels. Cargo holds that have been designated to cargo ships have been specially designed to enhance the processes of loading and unloading in order to keep containers safe while crossing the seas. There is a sophisticated hatch design to allow openings from the main deck to reach the cargo hold locations. These openings are situated along the entire cargo hold breadth, surrounded by a raised steel structure called the hatch coaming. The hatch coamings have hatch covers located on them. Tarps and wooden boards held down the battens and secured the hatches until the 1950s. Hatch covers are made of secure metal plates and cranes are used to lift them on and off of the ship. Additional hatch models use hydraulic rams and articulated mechanisms for closing and opening. Cell guides are another main component within container ship design. The cell guides are vertical pieces constructed of strong metal that is attached to the cargo hold within the ship. They work by guiding containers into particular rows while loading and help to support items during travel. The design of the container ship uses cell guides enough that the United Nations Conference on Trade and Development utilize them to distinguish between container ships and regular break-bulk cargo ships. There is a system used in cargo plans consisting of three dimensions to outline a container's position aboard the ship. The bay is the first coordinate, starting at the front of the container ship and increases aft. The tier is the second coordinate, with the initial tier staring at the bottom of the cargo holds with the second, tier situated on top of the first and continuing on. The row is the third coordinate. Rows are situated on the ship's port side have even numbers while those found starboard have odd numbers. Rows found along the centerline are given lower numbers and these numbers increase for slots situated further from the center. Container handlers carry 20, 40 and 45 foot containers. The largest size fits only above deck while the 40 foot size makes up for the majority of the load or approximately ninety percent of the container shipping. Approximately 90% of the freight moves across the globe with container shipping. It is estimated that 80% of global freight travels with 40-foot containers.